IBOC 300*

Features RCP8+

Features

IBOC 300

- Battery operated
- Single station
- Single program
- 1 to 3 start times per day
- Station run times (each program): 1 minutes to 23 hours,
 59 minutes; in 1 minute increments
- 4 irrigation cycle options: twice per day, once per day, once per two days and once every 7 days
- Programmable by hand or with optional infrared transmitter RCP8+
- Delay starts: 0 hours, 4 hours, 8 hours or 12 hours
- Retains program up to 2 minutes without battery installed
- Simple programming 3 watertight buttons
- LED lights confirm program input and verify operation
- Low power consumption 1 to 2 years battery duration
- International icon graphics with English captions for easy programming and manual operation
- Automatic and manual irrigation cycle capabilities
- Default program: 15 minutes of irrigation per day (just plug in the battery and walk away)
- Fits all Irritrol irrigation valves with internal manual bleed adapter VA12.
- 7 day calendar
- Accepts 1 of 8 programs stored in infrared IBOC RCP8+
- Programmable address allows easy programming with more than one IBOC 300 in a valve box
- LED lights flash to indicate successful program download.
- Waterproof cabinet **IP68** allows installation in valve boxes



IBOC 300

Specifications

IBOC 300

- 9V Alkaline battery (not included)
- Operating pressure: 1,4 10 bar (20,3 145 PSI)
- Operating temperature: from 0° up to 50°C
- Dimensions: 76 x 63 x 38 mm.



Code

| IBOC 300 | IBOC 300 |
|-----------|--------------------------------------|
| BAT 9 VDC | Battery case for standard 9V battery |
| RCP8+ | Infrared transmitter for IBOC 300 |

Adapters Code

| VA 12 | All Irritrol, Hit, Galcon and Bermad valves |
|-------|---|
| VA 15 | Rain Bird valves |
| VA 18 | Toro 252 valves |
| VA 20 | Nelson valves |



Features

RCP8+ Infrared Transmitter

- RCP8+ transmitter allows transmission of programs or review of the installed unit's program
- Infrared transmission up to 3 m
- 8 Programs can be stored and transmitted one by one
- 8 programs can be set to 8 different addresses
- Programmable "rain off" up to 7 days.

Specifications

IBOC RCP8+

- 4 "AAA" 1,5 V Alkaline batteries (not included)
- Sizes: 218 x 60 x 28 mm
- Weight: 175 grams



^{*} Until stock last