

PRO-VAN NOZZLES

ADJUSTABLE NOZZLES FOR HS AND SL

These nozzles offer the possibility to adjust arc in function of all needs as also reducing water waste. Furthermore, they fit HS and SL SprayHead offering superior uniformity.

Features

- Adjustable Arc nozzle from 0-360 degrees
- The arc is adjusted by rotating the top of the nozzle by hand
- The nozzle will come assembled in the 0 degree position in order for the end user to utilize the indicators on the top of the nozzle (the arrow on the top of the nozzle will indicate the watering pattern)
- Color coded for easy identification
- Filter included
- Stainless steel radius adjustment screw allows up to 25% radius adjustment.



PRO-VAN 8 PRO-VAN 10 PRO-VAN 12 PRO-VAN 15 PRO-VAN 17

Code

PRO-VANXX Adjustable nozzles from 0° to 360°

Adjustable Nozzle for HS and SL Performance chart

Adjustable nozzle	ARC	Pressure (bar)	Mod 8 ● Radius 2,4m		Mod 10 ● Radius 3,0m		Mod 12 ● Radius 3,7m		Mod 15 ● Radius 4,6m		Mod 17 ● Radius 5,1m	
			Flow Range (l/m)	Radius (m)	Flow Range (l/m)	Radius (m)	Flow Range (l/m)	Radius (m)	Flow Range (l/m)	Radius (m)	Flow Range (l/m)	Radius (m)
360°	1	6,8	2,1	7,2	2,7	9,2	3,0	10,0	4,1	12,0	4,3	
	1,5	8,0	2,4	9,6	3,0	10,8	3,4	12,0	4,3	14,0	4,8	
	2	9,6	2,4	10,8	3,0	12,0	3,7	14,0	4,6	16,0	5,1	
180°	1	3,4	2,1	3,6	2,7	4,6	3,0	5,0	4,1	6,0	4,3	
	1,5	4,0	2,4	4,8	3,0	5,4	3,4	6,0	4,3	7,0	4,8	
	2	4,8	2,4	5,4	3,0	6,0	3,7	7,0	4,6	8,0	5,1	
90°	1	1,7	2,1	1,8	2,7	2,3	3,0	2,5	4,1	3,0	4,3	
	1,5	2,0	2,4	2,4	3,0	2,7	3,4	3,0	4,3	3,5	4,8	
	2	2,4	2,4	2,7	3,0	3,0	3,7	3,5	4,6	4,0	5,1	

Data represent results in zero wind. Adjust for local conditions.
Radius may be reduced up to 25% with adjustment screw (this may alter the uniformity of the spray pattern).