

HS SPRAYHEAD



Features

- New redesigned bodies including 7.5, 10, 15, and 30 cm models.
- Heavy duty stainless steel retract spring ensures positive pop-down
- Ratcheting riser permits easy arc adjustment in the field
- Side and bottom inlets (6" and 12" models) reduce installation time
- Pressure activated seal cleans debris from stem, reduces flow by during pop-up and prevents leaking between cap and body

Specifications

- Recommended working pressure: 1,5 - 3 bar
- Precipitation rate: 35 - 55 mm/h
- Spacing: 1,8 - 4,6 m
- Inlet size: 1/2" Female NPT
- Exposed diameter: 47 mm

*The HS Spray head is supplied as the body alone.
The required nozzle codes must be specified on order*

Code

HS300	HS (3"), 7,5 cm pop-up height
HS400	HS (4"), 10 cm pop-up height
HS600	HS (6"), 15 cm pop-up height
HS1200	HS (12"), 30 cm pop-up height
HS500-CV	Check Valve
HS-1	Shrub Adapter

Optional Accessoires

CHECK VALVE

Features

- HS check valve extends system life by reducing negative effects of water hammer as also useful for installation on pending grounds
- Fits all pop-up heights: 7.5, 10, 15 and 30 cm.



HS00-CV

Specifications

- Maintains up to 2,5 m in elevation change.

SHRUB ADAPTER

Features

- Accepts all canopy nozzles
- Thread 1/2"
- UV treated for above-ground mount
- Manufactured of heavy-duty ABS
- Inlet size: 1/2" Female NPT threads.



HS-1