

## SL SERIES POP UP

### 2", 4" AND 6" MODELS

#### Features

- Compact slimline body design
- Available with pre-installed Variable Arc Nozzles in four radii (10', 12', 15' and 17')
- Matched precipitation rate nozzles provide even coverage
- Adjustable arc patterns from 25°-360°
- Debris labels on models without nozzles for easy flushing
- Pressure-activated seal reduces flow-by during pop up and keeps debris away from stem during retraction
- Heavy-duty, stainless steel retract spring ensures positive pop down
- One-piece molded body adds durability
- Removable nozzle, screen and internal components for flushing and servicing
- Accepts all Irritrol MPR Variable Arc Nozzles and Irritrol MPR Canopy™ fixed-arc nozzles
- Field-installable check valve (SL-CV) holds back up to seven feet of elevation change to prevent low-head drainage

#### Specifications

- Recommended working pressure: 1,5 - 3 bar
- Inlet size: 1/2" female NPT threads
- Exposed diameter: 31,8 mm
- Body height:
  - SL200: 10,5 cm
  - SL400: 15,5 cm
  - SL600: 20,5 cm



\* For performance data see HS Chart

#### Code

**SLPX 4 12**

Model	Riser Height	Van Nozzles Radius
SLPX 200	2" (5 cm)	00-w/o nozzle
SLPX 210	2" (5 cm)	10' (3 m)
SLPX 212	2" (5 cm)	12' (3,6 m)
SLPX 215	2" (5 cm)	15' (4,5 m)
SLPX 217	2" (5 cm)	17' (5,2 m)
SLPX 400	4" (10 cm)	00-w/o nozzle
SLPX 410	4" (10 cm)	10' (3 m)
SLPX 412	4" (10 cm)	12' (3,6 m)
SLPX 415	4" (10 cm)	15' (4,5 m)
SLPX 417	4" (10 cm)	17' (5,2 m)
SLPX 600	6" (15 cm)	00-w/o nozzle
SLPX 610	6" (15 cm)	10' (3 m)
SLPX 612	6" (15 cm)	12' (3,6 m)
SLPX 615	6" (15 cm)	15' (4,5 m)
SLPX 617	6" (15 cm)	17' (5,2 m)