

SLIM DIAL™

CONTROLLERS

6 station model (indoor)

Features

Flexible Programming

- Two independent programs
- Specific days-of-the-week or odd/even programming
- Station run times from 1 minute to 4 hours in 1-minute increments
- Two start times per program for up to four start times per day

Easy Operation

- Automatic, semi-automatic and manual operation
- Simple nine-position programming dial and large, self-prompting LCD
- 365-day calendar for days of the week or odd/even programming (adjusts for leap year)
- English/Spanish manual and quick-reference cards

Additional Features

- Battery backup keeps accurate time and maintains program during power failure
- Automatic safety backup program
- Master valve/pump start circuit

- Self-resetting circuit breaker protection
- Attractive, slim-line plastic cabinet
- Wiring skirt/conduit adapter hides wiring for professional installation
- 120 VAC plug-in transformer
- UL and CSA listed

- Maximum output to valves: 24 VAC, .50 amp
- Battery backup: 9-volt alkaline battery (not included)

Dimensions


Height: 6"
Width: 8 ½"
Depth: 2 ½"

Electrical Specifications

- Transformer input: 120 VAC, 60 Hz
- Transformer output: 24 VAC, .6 amp
- Maximum output per station: 24 VAC, .25 amp



MODELS HOW TO SPECIFY



Irritrol
SYSTEMS

BEYOND THE EXPECTED

5825 Jasmine Street, Riverside, CA 92504-1183
909/785-3623 Fax 909/785-3795
<http://www.irritrolsystems.com>