

KWIK DIAL™

Features

- 4, 6, 9 and 12 Stations in/out
- 3 independent programs allow differing water days, start times, station running times and station assignments
- Automatic, semiautomatic (manual program) and manual station(s) operation
- Flexible watering day schedules:
 - Any day-of-the-week watering
 - Automatic leap year and 31st day skip with odd/even programming
 - Excluded-day option allows selection of specific days(s) not to water
- "Program stacking" feature stores programs for sequential operation (prevents program overlap)
- Programmable "Rain Off" up to 7 days
- Dial and four pushbuttons for ease of programming
- Large LCD displays status of programs scheduled to run each day
- Sensor hookup with Sensor bypass switch
- Multiple language capabilities (English, French, German, Italian and Spanish)
- English or international icon face plate
- Built-in memory maintains real time and programming information for a minimum of 24 hours in the absence of AC power.
- Self-diagnostic, electronic circuit breaker identifies and overrides an electrical "short" in a valve or in valve wiring and continues to water operable stations
- "All-stations" test program
- Electrical surge protection (on both input and output lines) resists damage from lightning storms and power surges
- Water budgeting feature for each program (0-200% in 10% increments)
- Weather-resistant plastic case with internal transformer (outdoor model) and provision on door for a padlock
- Durable plastic case with plug-in transformer (indoor model)
- "Remote Ready"
- CE, UL and CUL listed.

Specifications

- Station run times: 1-240 minutes (four hours) in 1-minute increments.
- Start times: 3 per program for up to 9 daily starts
- Transformer input: 120 VCA, 60Hz or 230/240 VCA, 50 Hz
- Transformer output: 24 VCA .830 Amp
- Maximum output per station: 24 VCA, .4 Amp
- Maximum total output: 24 VCA, .8 Amp (including master valve)

Dimensions

<i>Outdoor</i>	Height: 230mm (9") Width: 172mm (67/8") Depth: 100mm (4")
<i>Indoor</i>	Height: 223mm (87/8") Width: 156mm (61/8") Depth: 76mm (3")



Code

KD4-INT-E	4 stations (external transformer)
KD6-INT-E	6 stations (external transformer)
KD9-INT-E	9 stations (external transformer)
KD12-INT-E	12 stations (external transformer)
KD4-EXT-E	4 stations (built-in transformer)
KD6-EXT-E	6 stations (built-in transformer)
KD9-EXT-E	9 stations (built-in transformer)
KD12-EXT-E	12 stations (built-in transformer)