

Sure to become a contractor favorite, the 430R rotor from Irritrol offers everything you would expect from a 1/2" rotor. When your application calls for more than ordinary sprayheads, but not enough for large rotors, we offer the 430R- the newest member of the Irritrol family. With a familiar arc setting and the ability to quick check the left and right stops, the 430R is sure to save time on installation. **Irritrol. Get more done.**

### Features

- Inlet: 1/2" female-threaded
- Adjustable arc range: 40 to 360°
- Flow range: 2,8 – 12,5 l/min
- Recommended operating pressure: 2 – 3,5 bar
- Maximum operating pressure: 4,2 bar
- Overall height (retracted): 15 cm
- Radius: 5,1 to 9,0 mt
- Standard nozzle trajectory: 25°
- 5 interchangeable nozzles
- Riser height: 10 cm



### GET MORE FOR LESS

- Familiar top adjustment, wet or dry**
- Reversing full and part circle operation**
- Pressure operated wiper seal**
- Wide selection of nozzles**
- Ability to quick check the arc**
- Ratcheting riser**
- Fixed right stop**
- Ideal for low flow application**
- Stainless steel adjustment screw**

### Performance Charts

Nozzle	Pressure (bar)	Radius (m)	FlowFlow (l/min)
0,75	2,0	5,1	2,8
	2,7	5,4	3,0
	3,4	5,4	3,4
1,0	2,0	6,0	3,4
	2,7	6,3	4,5
	3,4	6,3	4,9
1,5	2,0	6,9	5,3
	2,7	7,2	6,4
	3,4	7,2	7,2
2,0	2,0	7,5	6,8
	2,7	8,1	8,0
	3,4	8,1	9,1
3,0	2,0	8,4	10,2
	2,7	9,0	11,4
	3,4	9,0	12,5

### Code

430R

1/2" Gear-Driver  
Rotor

# Irritrol®

BEYOND THE EXPECTED

I.S.E. Via dell'Artigianato. 1-3  
00065 Fiano Romano (Roma)  
Tel. (+39) 0765/40191  
Fax (+39) 0765/455386  
www.irritrol.it