

200-B

Features

- Globe/angle configuration (G/A)
- Accepts Irritrol OmniReg pressure regulator
- Female thread BSP 1½” and 2” (NPT available on request)
- Flow Control (FC)
- Internal and external manual bleed
- Heavy-duty, corrosion and UV resistant PVC construction with stainless steel bonnet screws
- Screws accept phillips, flat-blade and hex driver tools
- O-ring gasket on unused inlet cap guarantees hermetic seal and does not require Teflon
- Reinforced top and base of body
- Captive Solenoid (the plunger is retained in the solenoid)
- Slow, anti water hammer closing
- Double-beaded diaphragm provides leak-proof seal
- Working pressure: 1,4 to 10 bar
- Solenoid 24VAC 50Hz (24VAC 60Hz on request)
 - Inrush current, 0,34 Amp.
 - Holding current, 0,20 Amp.

Code

216B-M	Serie 200-B 1 ½” FBSP G/A FC
217B-M	Serie 200-B 2” FBSP G/A FC



217B-M

Pressure loss (bar)

m³/h	4,8	6,0	7,2	8,4	9,6	10,8	12,0	15,0	18,0	21,0	24,0	27,0	30,0	33,0	36,0
l/min	80	100	120	140	160	180	200	250	300	350	400	450	500	550	600
1 ½” Globe	0,21	0,19	0,18	0,16	0,16	0,19	0,23	0,32	0,38	-	-	-	-	-	-
1 ½” Angle	0,19	0,17	0,15	0,14	0,15	0,15	0,21	0,25	0,30	-	-	-	-	-	-
2” Globe	-	0,14	0,13	0,12	0,12	0,11	0,11	0,13	0,20	0,29	0,36	0,43	0,51	0,62	0,74
2” Angle	-	0,14	0,13	0,12	0,12	0,11	0,11	0,12	0,15	0,19	0,25	0,33	0,61	0,61	0,61

*Irritrol Systems Europe S.r.l.
may change product specifications
without prior notice and without liability*